



**TECHNICAL DATA**

Square dimensions:	5x5 mm
Width:	100 cm
Length:	50 m
Color:	1302-050 white / 1303-050 orange
Material Warp/Shot:	C-glass
Treated fabric weight:	145 g/m <sup>2</sup>
Loss of ignition:	16%
Characteristics:	alkaliresistant, obstructing yarn drifting

**TENSILE STRENGTH PER 5 CM:**

Tensile strength warp (N/5cm):	mind. 1500 N
Tensile strength shot (N/5cm)	mind. 1700 N
Elongation:	2,5 - 3 %

**28 DAYS STORAGE TO 5% SODIUM HYDROXIDE:**

Tensile strength warp (N/5cm):	mind. 1000 N
Tensile strength shot (N/5cm)	mind. 1000 N
Elongation:	1.5 - 2 %

**Made in Europe**

**Item: 1302-050 white / 1303-050 orange**

**50 m<sup>2</sup> per roll / 33 rolls per pallet**

bringing european innovation



FOR MORE INFORMATION CONTACT: **Smet Building Products Ltd**

93A Belfast Road | Newry | BT34 1QH | Northern Ireland

T: +44 (0)28 3026 6833 ROI: +353 (0) 1697 8586

E: [info@smetbuildingproducts.com](mailto:info@smetbuildingproducts.com)

[www.smetbuildingproducts.com](http://www.smetbuildingproducts.com) or [www.smet.ie](http://www.smet.ie)



The information, and, in particular, the recommendations relating to the application and end-use of SMET distributed products, are given in good faith based on SMET's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with the manufacturer's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. The manufacturer reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request. DEC 24